

# CK2610

## Main Features

---

- **Engine Gross Power:** 24.5 hp (18.2 kW)
- **PTO Type:** Live
- **Transmission Type:** Manual
- **Shuttle:** Dry Dual Stage
  
- Diesel engine with Daedong ECO Technology
- Hydrostatic Power Steering
- Rear PTO
- Foldable ROPS
- Single Lever Joystick Standard
- High Capacity Hydraulic Pump
- Available with Field Option Cab

This post is also available in: [FR](#)

### Diesel engine with Daedong ECO Technology

The new 24.5 hp (18.2 kW) ECO-friendly diesel engine provides powerful performance and improves fuel efficiency while reducing noise levels.

The new 24.5 hp (18.2 kW) ECO-friendly diesel engine provides powerful performance and improves fuel efficiency while reducing noise levels.

### Power Steering

Responsive, powerful and comfortable steering reduces operator fatigue. The power steering system is robustly designed for maneuvering in soft soil and for front loader operation.

### Rear PTO

Rear PTO is standard and mid PTO is optional. You can select the rear or mid PTO separately or simultaneously.

### Foldable ROPS

A fold-down roll bar allows you to move into tight areas quickly and easily.

### Center Marker

The center marker on the hood assists with maintaining straight rows.

### High Capacity Hydraulic Pump

The high capacity, efficient tandem hydraulic pump gives you smoother handling in heavy-duty working conditions and helps to reduce operator fatigue.

### Deluxe Seat

A fully adjustable suspension seat allows the operator to ride in comfort no matter what the job. A retractable seatbelt is standard on all Kioti tractors to ensure operator safety.

### Single Lever Joystick

The operation of the front end loader is made easier by the use of a single lever joystick. The joystick allows you to perform all loader functions with a single lever. The lever automatically returns to neutral and the loader stops in place when the joystick is released. A float position allows the bucket free flotation over the ground surface.

### Simple Maintenance

Kioti tractors are designed for easy maintenance. Lifiable hoods and removable side panels allow convenient access for daily service checks. Maintaining your tractor for long life and high performance has never been easier.

### High Ground Clearance

The minimum ground clearance of 13.4 in. makes usage on rocky or uneven terrain simpler.

## **Illuminated Dashboard**

---

The illuminated dashboard ensures great visibility while working in bright daylight or at night. The operator can check important instrumentation at a glance with an easy-to-see tachometer, hour meter, fuel temperature gauge and battery charge lamp.

## **9x3 Manual Transmission**

---

Manual transmission models feature 9F/3R speeds with synchronized 2nd and reverse gears making repetitive back and forward operation more efficient.

Manual transmission models feature 9F/3R speeds with synchronized 2nd and reverse gears making repetitive back and forward operation more efficient.

## **Engine**

---

Engine Model	3A165LWM-U
Engine Gross Power	24.5 hp (18.2 kW)
Rated Speed	2,600 rpm
No. of Cylinders	3
Fuel Type	Diesel
Aspiration	Natural
Displacement	100.5 cu. in. (1,647 cc)
Fuel Tank Capacity	9.0 gal. (34 L)

## **Transmission**

---

Transmission Type	9x3 Manual Transmission
Main Gear	Manual
No. of Travel Speeds - Forward / Reverse	9F/3R
Min. Travel Speed of Forward w/ Ag @ Engine rated speed	0.94 mph (1.52 km/h)
Max. Travel Speed of Forward w/ Ag @ Engine rated speed	14.63 mph (23.56 km/h)

## **Power Take-Off (PTO)**

---

PTO Type Trans	Live
PTO Power	21.7 hp (16.2 kW)
Rear PTO Speeds (1st)	540 rpm
Mid PTO Speeds	2,000 rpm (optional)

## **Brakes and Clutch**

---

Brakes	Wet Multi Disc
Clutch	Dry Dual Stage

## **Dimensions w/ AG Tire**

---

Length w/ 3-point hitch	120.9 in. (3,070 mm)
Width	55.1 in. (1,400 mm)
Height from Top of ROPS	99.2 in. (2,520 mm)
Wheelbase	65.7 in. (1,670 mm)
Ground Clearance	13.4 in. (340 mm)
Front Tread Ag Tires - Min	44.6 in (1,132 mm)

Rear Tread Ag Tires - Min 51.3 in. (1,302 mm)  
 Min. Turning Radius w/ Brake 8.0 ft. (2.4 m)

**Hydraulics**

Total Pump Flow 11.7 gpm (44.4 L/min)

**3-Point Hitch**

Standard Category Category 1  
 Lift Capacity, 24" aft of hitch 1,631 lbs. (740 kg)  
 Control Type Position

**Weight**

Weight w/ Ag Tires w/ ROPS 2,646 lbs. (1,200 kg)

**Equipment & Panel**

**Standard Equipment**

- Headlights
- Signal Lamp
- Parking Brake
- Hydrostatic Power Steering
- Wet Multi Disc Brakes
- Single Lever Joystick
- Rear PTO
- Flip Up PTO Cover
- Illuminated Dashboard
- Rear External 3-Pt Control Lever
- Cup Holder

**Optional Equipment**

- Mid PTO Kit
- Rear Working Light
- Front Weight Kit
- Dual Remote Valves (2 Spring Valves)
- Dual Remote Valves (1 Detent Valve & 1 Spring Valve)
- Dual Remote Valves (2 Detent Valves)
- Sun Canopy
- Clevis Type Drawbar
- Tool Box
- Side View Mirror
- Telescopic Lower Link
- Dual Air Cleaner Element
- Deck Mat
- Lift Rod Kit
- Armrest Kit
- Horn
- Field Option Cab

**Instrument Panel**

- Digital Hour Meter
- Coolant Temperature Gauge
- Electrical Tachometer
- Fuel Gauge
- Engine Oil Pressure Light
- High Beam, Emergency Flasher, Direction Indicators
- Glow Plug Light
- Alternator Light

**Available Tires**



**Agriculture**

Front 7-16  
 Rear 11.2-24



**Turf**

Front 28x8.5-15/6  
 Rear 41x14-20/4



**Industrial**

Front 27X8.5-15  
 Rear 15-19.5